

FHD-1107

Filmax Dissolved Water Removal Filter
Direct cross for SD-1107

Applications

- Hydraulic
- Compressor
- Insulating
- Turbine
- Transmission Oil



Performance Data

- Viscosity 100-500 SUS
- Collapse Pressure Rating 75 PSI
- Maximum Temperature 275 F
- Direction of Flow Outside-In
- Water Removal 1300 ml

Dimensional Data

- Outer Diameter 11"
- Inner Diameter 2 1/8"
- Length 7 1/2"

Shipping Data

- Number Per Case 1
- Shipping Weight 22 lbs

Part #	Case Qty
FHD 1107	1
Fits these Housings:	
Filmax F-3000, Velcon VF-12 Series, Cuno PT1 style, Alsop	
Flow rate	
10 GPM or less	

Physical Data

- Handle Plated Steel
- Seal Material BUNA-N
- Type of Adhesive Epoxy
- Type of Endcap Plated Steel

Please Note

Using differential pressure to measure the performance of the Filmax FHD filter will not provide optimal results, however it can be confirmed by several methods. The amount of dissolved water removed by the filters can be assessed utilizing in-line moisture sensors such as the Doble Domino, by means of Dissolved Gas Analysis (DGA), or by using a Karl Fischer test.