

FHF2130-WAGON

1800GPH

APPLICATIONS

Hydraulic Oil • Compressor Oil • Quench Oil • EDM Oil • Lubricating Oil • Insulating Oil • Turbine Oil



SPECIFICATIONS

- Heavy-duty TEFC 2 HP 230 Vac 1 phase Baldor motor.
- 30 GPM Positive Displacement Mechanical Seal Gear Pump with Internal Relief Valve.
- One (1) Polyurethane Powder Baked FHF3000 High-Flow Housing.
- Wired 230 VAC, 1 phase with all electrical components mounted in a NEMA 12 enclosure.
- Automatic High-Pressure Shutdown System for unattended operation.
- Plumbed with all brass and black iron fittings.
- 1 1/2" inlet and outlet ports with male Cam Loc fittings.
- Fifteen (15) feet of Heavy Duty 14/3 Power Cable.
- Manufactured with a two (2) port manifold for multiple filtering and fluid transferring configurations.
- Suction-Wye Strainer to protect pump from large debris.
- 0-100 PSI Glycerin Filled Gauge for monitoring system pressure.
- Inline aluminum resettable flow Totalizer.
- Stationary skid mount design manufactured for dedicated high flow filtration.
- Vessel manufactured to accept most standard pleated filters.



