



**Filmmax**<sup>™</sup>  
Oil Filtration Systems

# FF300-UPO

PARTICULATE ONLY FILTER ELEMENT

**\*\*VARIOUS MICRON OPTIONS AVAILABLE\*\***

## Performance Data :

MICRON RATING: TBD

COLLAPSE PRESSURE RATING: 75 PSI

MAXIMUM TEMPERATURE: 250F

DIRECTION OF FLOW: OUTSIDE /IN

RECOMMENDED CHANGEOUT

DIFFERENTIAL PRESSURE: 30 PSI

## Dimensional Specifications:

OUTER DIAMETER, TOP: 11.00"

OUTER DIAMETER, BOTTOM: 11.00"

INNER DIAMETER, TOP: 2.125 "

INNER DIAMETER, BOTTOM: 2.125"

LENGTH: 7.188"

## Physical Specifications :

HANDLE: YES

SEAL MATERIAL: BUNA N

TYPE OF ADHESIVE: N/A

TYPE OF ENDCAP: MOLDED EPOXY

CENTER TUBE: PLATED STEEL

MEDIA: PROPRIETARY

WATER-ABSORBENT

AREA: 1695 SQ IN

CONFIGURATION: DOE

## Packaging Specifications

NUMBER PER CASE: 1

WEIGHT PER CASE: 8 LBS

## UTILITY SPECIFIC FILTER ELEMENT

ADVANCED FILTER

SPECIFICALLY DESIGNED

FOR SUBSTATION APPLICATIONS

- TRANSFORMER OIL (INSULATING OIL)
  - SILICONE OIL
- ESTER-BASED OILS (NATURAL AND SYNTHETIC)
  - MINERAL OIL FOR CIRCUIT BREAKERS
    - VACUUM OIL
  - DIELECTRIC FLUIDS



## KEY FEATURES

MITIGATES PARTICULATE/CARBON