



**Filmmax**<sup>™</sup>  
Oil Filtration Systems

# FF300KSA-US

**\*NEW PRODUCT THAT REPLACES FF300KSA FILTER\***

**\*\*PLEASE NOTE\*\***

As of January 2025, the FF300KSA filter is obsolete.  
Filmmax has designed and produced the FF300KSA-US as the  
direct replacement.



## Performance Data :

MICRON RATING: 3 MICRON  
COLLAPSE PRESSURE RATING: 75 PSI  
MAXIMUM TEMPERATURE: 250F  
DIRECTION OF FLOW: OUTSIDE /IN  
RECOMMENDED CHANGEOUT  
DIFFERENTIAL PRESSURE: 30 PSI

## Dimensional Specifications:

OUTER DIAMETER, TOP: 11.00"  
OUTER DIAMETER, BOTTOM: 11.00"  
INNER DIAMETER, TOP: 2.125 "  
INNER DIAMETER, BOTTOM: 2.125"  
LENGTH: 7.188"

## Physical Specifications :

HANDLE: YES  
SEAL MATERIAL: BUNA N  
TYPE OF ADHESIVE: N/A  
TYPE OF ENDCAP: MOLDED EPOXY  
CENTER TUBE: PLATED STEEL  
MEDIA: PROPRIETARY  
WATER-ABSORBENT  
AREA: 1695 SQ IN  
CONFIGURATION: DOE

## Packaging Specifications

NUMBER PER CASE: 1  
WEIGHT PER CASE: 14 LBS

**UTILITY SPECIFIC FILTER ELEMENT**  
ADVANCED INSULATING OIL FILTER SPECIFICALLY  
DESIGNED FOR SUBSTATION APPLICATIONS



## **KEY FEATURES**

MITIGATES FREE WATER, DISSOLVED  
WATER, AND PARTICULATE/CARBON.